# CANNAFREEZE

"Enhancing Product Quality & Profits"

**CANNABIS FREEZE DRYER** "Stainless Programmable"



MODEL FC 50 +

**PRICED AT \$194,995** 

15 KW CHILLER (APPROXIMATELY 80 LBS/24 - 36 HOURS)

This is the newest concept in a programmable, food grade freeze dryer built to exacting specifications for the cannabis and hemp industries.

The FC 50 freeze dryer is a short cycle, high performance unit featuring stainless steel shelves conducting heat directly to the product. Freeze drying conduction does not require high shelf temperatures and is instrumental in retaining cannabinoids.

### Some of the key features of this unit are:

- Fast drying capabilities of 24 36 hours for approximately 80 lbs. depending on product type
- o Fully programmable automatic cycle with 19 Inch touch screen HMI
- o Remote access via internet and direct factory support
- Shelf area of 54 Sq Feet and a shelf spacing of 2.36 Inches
- Fast initial product freezing via conduction
- The refrigeration system is water cooled, and a 15 kw chiller is supplied with the freeze dryer.

The Model FC 50 is also ideal for large scale product development and small scale production activities.

**Built to exacting specifications at** our ISO:9001 Factory.

Onsite commissioning will be completed by a CannaFREEZE team member.

#### TECHNICAL DATA **FC 50**

ICE CONDENSER CAPACITY:	165 lbs
ICE CONDENSER PERFORMANCE:	132 lbs/24 Hrs
ICE CONDENSER TEMPERATURE:	-76°F
DEFROST:	Hot Gas
SHELF DIMENSIONS:	25.6 x 31.5 Inches
NUMBER OF SHELVES:	8 + 1 (16 Trays)
SHELF AREA:	54 Sq Feet
SHELF SPACING:	2.36 Inches
SHELF TEMPERATURE:	-58°F to +194°F
COOLING SYSTEMS:	Water Cooled
REFRIGERATION:	Two Stage
UNIT DIMENSIONS:	83 x 63 x 98 ln
	HxWxL
REFRIGERANT:	R-404A (NON-CFC)
VACUUM:	Pfeiffer Duo 35
<b>ELECTRICAL SPECS:</b>	460/480 Volt
	50/60 Cycle
	3 Phase + Ground
AMPERAGE:	40 Amp
WEIGHT:	3,908 lbs
FREIGHT:	Crated/Ocean







"Enhancing Product Quality & Profits"

**CANNABIS FREEZE DRYER** "Stainless Programmable"

**STANDARD** 





## **GENERAL DATA**

15 KW CHILLER	
COOLING CIRCUITS	1
COMPRESSORS	1 – Scroll
CAPACITY CONTROL	0-100%
POWER	460/3/60
FANS	1 – Axial
CONDENSER AIR FLOW	3,590 cfm
POWER (EACH)	0.76 kW
AVAILABLE STATIC PRESSURE	0 "wc
TANK VOLUME	30.4 gal
LENGTH	51.6 in
WIDTH	26 in
HEIGHT	55.1 in
WEIGHT	765 lb
AMPERAGE	13 A

## **PERFORMANCE**

15 KW CHILLER	
REFRIGERANT	R410A
HYDRAULIC KIT	P3
INLET WATER TEMPERATURE	69°F
<b>OUTLET WATER TEMPERATURE</b>	59°F
GLYCOL TYPE	25% Propylene Glycol
AMBIENT TEMPERATURE	95°F
COOLING CAPACITY	5.12 Tons 61,440 Btu/Hr
TOTAL ABSORBED POWER	6.33 kW
EVAPORATOR WATER FLOW RATE	12.8 gpm
AVAILABLE HEAD PRESSURE	39 psi
MAX AMBIENT TEMPERATURE	108°F

